U.S. DEPARTMENT OF COMMERCE
National Technical Information Service

PB-258 353

Assessment of Acetylene as a Potential Air Pollution Problem. Volume I

GCA Corp, Bedford, Mass GCA Technology Div

Prepared for

Environmental Protection Agency, Research Triangle Park, N C

Jan 76

BEST SELLERS

FROM NATIONAL TECHNICAL INFORMATION SERVICE

NTIS

Product Liability Insurance: Assessment of Related Problems and Issues. Staff Study
PB-252 204/PAT 181 p PC$9.50/MF$3.00

Evaluation of Home Solar Heating System
UCRL-51 711/PAT 154 p PC$8.75/MF$3.00

Developing Noise Exposure Contours for General Aviation Airports
ADA-023 429/PAT 205 p PC$7.75/MF$3.00

Cooling Tower Environment, 1974. Proceedings of a Symposium Held at the University of Maryland Adult Education Center on Mar. 4-6, 1974
CONF-74 0302/PAT 648 p PC$13.60/MF$3.00

Biological Services Program. Fiscal Year 1975
PB-251 736/PAT 52 p PC$4.50/MF$3.00

An Atlas of Radiation Histopathology
TID-26-676/PAT 234 p PC$7.60/MF$3.00

Federal Funding of Civilian Research and Development. Vol. 1. Summary
PB-251 266/PAT 61 p PC$4.50/MF$3.00

Federal Funding of Civilian Research and Development. Vol. 2. Case Studies
PB-251 683/PAT 336 p PC$10.00/MF$3.00

Handbook on Aerosols
TID-26-608/PAT 141 p PC$8.00/MF$3.00

for the Assessment of Ocean Outfalls
ADA-023 514/PAT 34 p PC$4.00/MF$3.00

Guidelines for Documentation of Computer Programs and Automated Data Systems
PB-250 867/PAT 54 p PC$4.50/MF$3.00

NOx Abatement for Stationary Sources in Japan
PB-250 586/PAT 116 p PC$5.50/MF$3.00

U.S. Coal Resources and Reserves
PB-252 752/PAT 16 p PC$3.50/MF$3.00

Structured Programming Series. Vol. XI. Estimating Software Project Resource Requirements
ADA-016 416/PAT 70 p PC$4.50/MF$3.00

Assessment of a Single Family Residence Solar Heating System in a Suburban Development Setting
PB-246 141/PAT 244 p PC$8.00/MF$3.00

Technical and Economic Study of an Underground Mining, Rubblization, and in Situ Retorting System for Deep Oil Shale Deposits. Phase I Report
PB-249 344/PAT 223 p PC$7.75/MF$3.00

A Preliminary Forecast of Energy Consumption Through 1985
PB-251 445/PAT 69 p PC$4.50/MF$3.00

HOW TO ORDER

When you indicate the method of payment, please note if a purchase order is not accompanied by payment, you will be billed an addition $5.00 *ship and bill* charge. And please include the card expiration date when using American Express.

Normal delivery time takes three to five weeks. It is vital that you order by number or your order will be manually filled, insuring a delay. You can opt for *airmail delivery* for a $2.00 charge per item. Just check the *Airmail Service* box. If you're really pressed for time, call the NTIS Rush Order Service (703) 557-4700. For a $10.00 charge per item, your order will be airmailed within 48 hours. Or, you can pick up your order in the Washington Information Center & Bookstore or at our Springfield Operations Center within 24 hours for a $6.00 per item charge.

You may also place your order by telephone or TELEX. The order desk number is (703) 557-4650 and the TELEX number is 89-9405.

Whenever a foreign sales price is NOT specified in the listings, all foreign buyers must add the following charges to each order: $2.50 for each paper copy; $1.50 for each microfiche; and $10.00 for each Published Search.

Thank you for your interest in NTIS. We appreciate your order.

METHOD OF PAYMENT

- ☐ Charge my NTIS deposit account no._____
- ☐ Purchase order no._____
- ☐ Check enclosed for $_____
- ☐ Charge to my American Express Card account number

Card expiration date_____

Signature_____

☐ Airmail Services requested

NAME_____

ADDRESS_____

CITY, STATE, ZIP_____

Item Number	Quantity: Paper Copy (PC)	Quantity: Microfiche (MF)	Unit Price*	Total Price*
			Sub Total	
			Additional Charge	
			Enter Grand Total	

All Prices Subject to Change
11/76

Clip and mail to

NTIS
National Technical Information Service
U.S. DEPARTMENT OF COMMERCE
Springfield, Va. 22161
(703) 557-4650 TELEX 89-9405

PB 258 353

REPRODUCED BY
NATIONAL TECHNICAL
INFORMATION SERVICE
U. S. DEPARTMENT OF COMMERCE
SPRINGFIELD, VA. 22161

TECHNICAL REPORT DATA
(Please read Instructions on the reverse before completing)

1. REPORT NO.	2.	3. RECIPIENT'S ACCESSION NO.
4. TITLE AND SUBTITLE Assessment of Acetylene as a Potential Air Pollution Problem		5. REPORT DATE January 1976 6. PERFORMING ORGANIZATION CODE
7. AUTHOR(S) Robert M. Patterson Eric Garshick Mark I. Bornstein		8. PERFORMING ORGANIZATION REPORT NO.
9. PERFORMING ORGANIZATION NAME AND ADDRESS GCA Corporation GCA/TECHNOLOGY DIVISION Bedford, Massachusetts		10. PROGRAM ELEMENT NO. 11. CONTRACT/GRANT NO. 68-02-1337
12. SPONSORING AGENCY NAME AND ADDRESS Environmental Protection Agency Office of Air and Waste Management Office of Air Quality Planning and Standards Research Triangle Park, North Carolina 27711		13. TYPE OF REPORT AND PERIOD COVERED Final 14. SPONSORING AGENCY CODE
15. SUPPLEMENTARY NOTES		

16. ABSTRACT

This report is one of a series which assesses the potential air pollution impacts of 14 industrial chemicals outside the work environment. Topics covered in each assessment include physical and chemical properties, health and welfare effects, ambient concentrations and measurement methods, emission sources, and emission controls. The chemicals investigated in this report series are:

Volume I	Acetylene	Volume VIII	Formaldehyde
Volume II	Methyl Alcohol	Volume IX	Methyl Methacrylate
Volume III	Ethylene Dichloride	Volume X	Ortho-Xylene
Volume IV	Benzene	Volume XI	Maleic Anhydride
Volume V	Acetone	Volume XII	Dimethyl Terephthalate
Volume VI	Acrylonitrile	Volume XIII	Adipic Acid
Volume VII	Cyclohexanone	Volume XIV	Phthalic Anhydride

17. KEY WORDS AND DOCUMENT ANALYSIS

a. DESCRIPTORS	b. IDENTIFIERS/OPEN ENDED TERMS	c. COSATI Field/Group
Acetylene Ambient Concentrations Health Effects Measurement Methods Chemical Properties Emission Sources Welfare Effects Emission Controls Industrial Chemicals Physical Properties	Acetylene Air Pollution Assessment Air Pollution Control Organic Chemicals	

18. DISTRIBUTION STATEMENT	19. SECURITY CLASS (This Report)	21. NO. OF PAGES
Unlimited	Unclassified	21
	20. SECURITY CLASS (This page)	22. PRICE
	Unclassified	3.50

EPA Form 2220-1 (9-73)

PRICES SUBJECT TO CHANGE

GCA-TR-75-32-G(1)

ASSESSMENT OF ACETYLENE AS A POTENTIAL AIR POLLUTION PROBLEM

Volume I

by

Robert M. Patterson
Mark I. Bornstein
Eric Garshick

GCA CORPORATION
GCA/TECHNOLOGY DIVISION
Bedford, Massachusetts

January 1976

Contract No. 68-02-1337
Task Order No. 8

EPA Project Officer
Michael Jones

EPA Task Officer
Justice Manning

U.S. ENVIRONMENTAL PROTECTION AGENCY
Research Triangle Park
North Carolina 27711

This report was furnished to the U.S. Environmental Protection Agency by the GCA Corporation, GCA/Technology Division, Bedford, Massachusetts 01730, in fulfillment of Contract No. 68-02-1337, Task Order No. 5. The opinions, findings, and conclusions expressed are those of the authors and not necessarily those of the U.S. Environmental Protection Agency or of the cooperating agencies. Mention of company or product names is not to be considered as an endorsement by the U.S. Environmental Protection Agency.

ABSTRACT

This report is one of a series which assesses the potential air pollution impacts of 14 industrial chemicals outside the steel industry. Topics covered in each assessment include physical and chemical properties, health and welfare effects, ambient concentrations and measurement methods, emission sources, and emission controls. The chemicals investigated in this report series are:

Volume I	Acetylene
Volume II	Methyl Alcohol
Volume III	Ethylene Dichloride
Volume IV	Benzene
Volume V	Acetone
Volume VI	Acrylonitrile
Volume VII	Cyclohexanone
Volume VIII	Formaldehyde
Volume IX	Methyl Methacrylate
Volume X	Ortho-Xylene
Volume XI	Maleic Anhydride
Volume XII	Dimethyl Terephthalate
Volume XIII	Adipic Acid
Volume XIV	Phthalic Anhydride.

CONTENTS

		Page
Abstract		iii
List of Tables		v
Sections		
I	Summary and Conclusions	1
II	Air Pollution Assessment Report	2
	Physical and Chemical Properties	2
	Health and Welfare Effects	2
	Ambient Concentrations and Measurements	6
	Sources of Acetylene Emissions	9
	Acetylene Emission Control Methods	11
III	References	12

TABLES

No.		Page
1	Signif[illegible] Properties of Acetylene	3
2	Effect [illegible] ne and Ethylene on Plants	5
3	Acetyle[illegible] ation For End Products	10
4	Acetyle[illegible] rs	10
5	Estimat[illegible] led and Operating Costs for [illegible] rber Scrubber	11

SECTION I

SUMMARY AND CONCLUSIONS

Pure acetylene is relatively nontoxic to man. It acts as a simple asphyxiant and produces ill effects only by reducing available oxygen. A concentration of 10 percent produces only slight intoxication, and there is no evidence of adverse effects from chronic exposure. Some damage will occur to sensitive plants at concentrations of the order of 100 ppm. Acetylene does not appear to be a significant component of photochemical smog.

Emissions of acetylene are estimated to have been 9 million pounds in 1974. These occur only from manufacturing and end use. Acetylene production and consumption have declined 47 percent since 1966 to a current production of 617 million pounds per year. Although there are no specific processes mentioned in the literature for the control of acetylene emissions, absorber/scrubber systems are used in manufacturing operations for product purification.

Simple diffusion model calculations place maximum expected 1-hour average ambient concentrations at about 5.5 ppm, and at about 3 ppm for 24-hour values near a plant boundary. Urban concentrations of about 80 ppb and rural values of 1 ppb have been measured.

Based on the low toxicity and expected low ambient concentrations, it appears that acetylene does not pose a health or environmental hazard as an air pollutant. Phosphine, a poisonous gas, is often-present as an impurity with acetylene, but at such low concentrations (less than 0.06 percent of the mixture) that it generally poses no hazard.

SECTION II

AIR POLLUTION ASSESSMENT REPORT

PHYSICAL AND CHEMICAL PROPERTIES

Pure acetylene is a colorless, odorless gas made up of carbon and two triple-bonded carbon atoms. Commercially it is made by the hydrolysis of calcium carbide, by thermal cracking of natural gas, and by combustion of natural gas. Acetylene obtained from the calcium carbide process, the most widely used method of manufacture, has a garlic-like odor due to contaminating phosphine, hydrogen sulfide, and ammonia produced from calcium carbide impurities. The oxygen-acetylene torch is used for welding and cutting of metal. The reactive triple bond makes acetylene an ideal starting material for the synthesis of chloride vinyl plastics, rigid plastics, paints, and chlorinated hydrocarbon solvents. Selected physical and chemical properties are presented in Table 1.

HEALTH AND WELFARE EFFECTS

Effects on Man

Acute Poisoning - Pure acetylene is relatively nontoxic. Only at high concentrations does inhalation of the gas begin to affect man, as shown below:[2]

Concentration	Response
100,000 ppm (10%)	Slight intoxication
200,000 ppm (20%)	Marked intoxication
300,000 ppm (30%)	Incoordination
350,000 ppm (35%)	Unconsciousness in 5 minutes

TABLE 1. SIGNIFICANT PROPERTIES OF ACETYLENE

Synonyms	Ethine, ethyne, [illegible]
Chemical formula	C_2H_2
Molecular weight	26.04
Boiling point (sublimes)	-83.6°C
Melting point	-81.8°C
Vapor density	0.9073 (dry air = 1)
Solubility	1.1 volumes of gas per volume of water at 15.5°C The gas is soluble in many organic materials.
Explosive limits	2.5% to 85% in air 2.82 to 93% in oxygen
Auto ignition temperature	Varies with impurities
Pure grade	640°C (100% gas)
Commercial grade	300°C minimum for mixtures of 30-70% in air. Concentrations other than these require higher ignition temperatures.
At 25°C and 760 mm	1 ppm = 1.065 mg/m^3 1 mg/m^3 = 0.939 ppm

The gas acts as a simple asphyxiant, producing ill effects in man only due to a diminished oxygen concentration in the ambient air. Recovery is complete upon removal from the gas. There is no hazard from skin or eye contact, and ingestion is impossible.

Illnesses attributed to acetylene exposure during welding have not been substantiated due to the presence of other hazardous materials, such as metal fumes.[3] With a lower explosive limit of 2.5 percent in air, it is clear that in the presence of a flame, an explosion would occur long before the acetylene could have any effect on man. Two reported deaths[4,5] attributable to acetylene generators were due to phosphine impurities in one case, and a combination of phosphine and acetylene asphyxiation in

the second case[illegible] the second case, it was est[illegible]hat the operator was exposed to [illegible]ent acetylene, resulting [illegible]ious ness and asphyxiation.

Acetylene has been used as an anesthetic, and [illegible] administered both intravenously [illegible] in a saline solution, [illegible] under controlled conditions at [illegible] concentration in air, [illegible] has been inhaled at 25 percent concentration to measure [illegible] elimination rate in patients with heart or lung disease as an indication of cardiac or pulmonary output.[6] Acetylene is soluble in like tissue with no ill effects.[7]

NIOSH has not established a recommended maximum allowable atmospheric concentration value for acetylene. However, the atmospheric concentration should be maintained below 5000 ppm to reduce the hazard of an explosion, or maintained at a lower value depending on the presence of impurities. In the United States raw materials are selected such that carbide-produced acetylene will not contain more than 0.05 percent phosphine, with actual concentrations usually in the vicinity of 0.00025 percent. Since the NIOSH recommended time weighted average value for exposure to phosphine is 0.3 ppm,[8] acetylene containing 0.05 percent phosphine could have maximum ambient concentration of approximately 500 ppm acetylene.[5]

Chronic Poisoning - There is no evidence that chronic exposure to acetylene at tolerable levels has any ill effects on man.[5]

Effects on Animals - Acute and Chronic Poisoning

Animal exposure to acetylene has not been documented. However, as in man, acetylene will act as an asphyxiant only at high concentrations, depriving the animal of oxygen.

Effects on Vegetation

Acetylene will produce abscission (separation of flowers, fruit, or leaves), epinasty (bending of leaves), and inhibition of growth in sensitive plants. Its toxicity to plants is related to that of ethylene which is widely regarded as the hydrocarbon most toxic to vegetation. Ethylene is a naturally produced plant hormone, active in the regulation of growth, development, and related processes such as the ripening of fruit. Exposure to higher than the biologically permitted levels can result in growth retardation, epinasty or abscission and discoloration of plant parts. Unsaturated hydrocarbons such as acetylene act as ethylene analogues, but must be present in much higher concentrations to produce the identical toxic effects. Atmospheric gases are taken up by plants through their leaves. Thus a primary result of acetylene and ethylene action is the discoloration, abnormal growth, and/or death of plant leaves. No characteristic markings are produced as is the case with sulfur dioxide, ozone, photochemical smog, or fluorides.

Acetylene doses and plant response are presented in Table 2. The concentration of ethylene needed to produce the same response is included as reference.

Table 2. EFFECT OF ACETYLENE AND ETHYLENE ON PLANTS[10,11,12]

Plant	Concentration, ppm		Duration	Response
	Acetylene	Ethylene		
Red kidney bean	125	0.1	4 hours	Abscission
Tomato	50	0.1	2 days	Epinasty
Pea stem	280	0.1	Rate comparison	Growth inhibition
Pea seedlings	250	0.2	3 days	Decimation

Reproduced from best available copy.

bscission was dete ined after 6 hours, and re he half maximal
bscission produced mpared to a control.[10] atio of 10,000 ppm
reduced the imal bscission, 65 percent, after hours. A study of the
inetics of r inhibition of the pe ed t ,800 times
ore acetyl was de produce the hibi produced
y ethylene.

ther Effect

ffects on - Acetylene will react with copper, silver, and mer-
ury to form explosive heavy metal ides. Its reaction
with the halogens, especially chlorine and fluorine, is rapid and explosive.[5]

Effects on Photochemical Smog - It has been well documented that reactions taking place between hydrocarbons and nitrogen oxides in photochemical smog produce ozone and peroxyacyl nitrate (PAN), two chemical species injurious to man, animals, plants, and various materials. Acetylene is not photochemically reactive enough or present in sufficient concentrations in the ambient air to contribute significantly to the atmospheric production of ozone and PAN.[13,14]

AMBIENT CONCENTRATIONS AND MEASUREMENTS

Measurements of acetylene in air have been made in Riverside, California, with morning values of 78 ppb and afternoon values of 27 ppb reported.[15] In contrast, concentrations of about 1 ppb were measured in "pure mountain air" near Riverside. Estimates of likely maximum concentrations near a production facility are presented below.

Ambient Concentration Estimates

The largest production facility for acetylene has a capacity of 180 million pounds per year. Assuming a 1.5 percent loss, this converts to an emission rate of

$$\frac{0.015 \text{ emission}}{5.36 \times 10^{7} \text{ sec/yr}} \times \frac{(180 \times 10^{6} \text{ lb/yr})}{(453.6 \text{ g/lb})}$$

of acetylene.

Some assumptions must be made regarding the characteristics of this acetylene release to the atmosphere.

In the first place, it is assumed that the concentrations of acetylene are likely to be highest around production facilities. Secondly, the acetylene emissions do not all come from one source within the plant, but rather from the numerous points of leakage in the facility. Thus the emissions can be characterized as coming from an area source which will be taken to be 200 meters on a side. Finally, the emissions do not occur at ground level, but at different heights, and an average emission height of 10 meters is chosen as a characteristic value.

Ground level concentrations can then be estimated at locations downwind of the facility.[16] To do this a virtual point source of emissions is assumed upwind of the facility at a distance where the initial horizontal dispersion coefficient equals the length of a side of the area divided by 4.3. In this case:

$$\sigma_{yo} = 200\text{m}/4.3 = 23.3\text{m}$$

Assuming neutral stability conditions (Pasquill-Gifford Stability Class D) with overcast skies and light winds, the upwind distance of the virtual

point source is approximately 310 meters. With consideration of the plant boundary, it is reasonable to assume that the nearest receptor location is then about 500 meters from the virtual point source. Finally, taking 2 m/sec as an average wind speed, the ground level concentration may be calculated from:

$$\chi = \frac{Q}{u\pi\sigma_y\sigma_z} e^{-\frac{1}{2}\left(\frac{H}{\sigma_z}\right)^2}$$

or

$$\chi = \frac{38.8}{(2)\pi(36)(18.5)}$$

$$= 8.01 \times 10^{-3} \text{ g/m}^3$$

for a 10-minute average concentration. Over a period of an hour this becomes:

$$8.01 \times 10^{-3} \text{ g/m}^3 \text{ (0.72)} = 5.77 \times 10^{-3} \text{ g/m}$$

or 5.5 ppm 1-hour average concentration at the plant boundary (190 m). Over a 24-hour period, the average concentration might roughly be expected to be about 3 ppm.

Measurement Technology

Acetylene at ambient air concentrations may be determined by wet chemical[17] or gas chromatographic[18] techniques. The former method will detect concentrations of between 10 ppb and 10 ppm, while the latter method will detect concentrations as low as 0.01 ppm and can be modified to detect acetylene concentrations to 0.1 ppb by volume.

In the first technique, acetylene is collected by absorption on silica gel contained in a narrow glass tube cooled by dry ice. A pink to red color is developed in the silica gel by addition of ammoniacal cuprous chloride and hydroxylamine hydrochloride. Concentrations of acetylene are determined by comparing the resulting color with colors of tubes containing known concentrations. This method provides reliable results at low concentrations, but the need for handling dry ice in the field makes the method somewhat cumbersome. Also, the method is not specific for acetylene but will determine any alkyne with the triple bond occurring at the end of the chain.

The gas chromatographic method is simpler to perform. Either integrated or grab samples may be collected for subsequent analysis in the lab. A portion of the air sample is injected into a chromatograph column from which it enters a flame ionization detector. The presence of acetylene is determined by its characteristic retention time, and concentrations are determined by comparing the peak height of the recorder response to heights produced by known concentrations.

SOURCES OF ACETYLENE EMISSIONS

Acetylene Production and Consumption

The consumption of acetylene has steadily dropped, for the last 5 years, from 1,161 million pounds in 1966 to 617 million pounds in 1974.[19,20] Competition from other less expensive raw materials has caused the decrease in acetylene consumption. Little, if any, growth is predicted for the future. Approximately 10 percent is used for welding, scarfing and cutting operations and the remainder as a chemical intermediate. Table 3 presents estimated consumption of acetylene for various end products.

Presently five companies with seven locations are manufacturing acetylene from other hydrocarbon sources (see Table 4). The number of locations producing calcium carbide acetylene is estimated to exceed 100 sites.

ACETYLENE CONSUMPTION FOR [illegible] UCTS

	Million [illegible] ear
[illegible] oride	183
e	153
[illegible] ntrile	90
	80
[illegible] roethylene	45
[illegible] acid and ester	28
[illegible] roethylene	8
	10
	607

[illegible] ble 4. ACETYLENE PRODUCERS[a]

Company	Location	[illegible] city, million pounds/year
Dow	Freeport, Texas	15
Monochem	Geismas, La.	180
Rohm and Haas	Deer Park, Texas	35
Tenneco	Houston, Texas	100
Union Carbide	Seadrift, Texas	20
Union Carbide	Taft, La.	12
Union Carbide	Texas City, Texas	25
Total		387

[a]July 1974. Not including producers using the carbide process.

Acetylene Sources and Emissions

Very little data exist in the literature concerning acetylene emissions. Based on other chemical processes, it is estimated that 1.5 percent of

total production is lost,[21] resulting in 9 million pounds of emissions. Primary sources of acetylene emissions are acetylene production and end product manufacturing. Acetylene is produced from natural gas or petroleum derivatives by partial oxidation or by electric arc processes, and also by the reaction of calcium carbide with water. This last method accounts for 38 percent of total production. Its 38 million pounds (10 percent) of acetylene used for welding and cutting is believed to be produced entirely by the calcium carbide method.

Since acetylene is an extremely flammable gas (explosive between concentrations of 2.5 percent and 85 percent), special precautions are taken during its handling and distribution. It is stored in steel cylinders at 250 psi pressure dissolved in acetone. Because there is no venting of the storage tanks, emissions from storage and handling are negligible. Production and end product manufacturing are believed to be the only significant sources of acetylene emissions.

ACETYLENE EMISSION CONTROL METHODS

Presently there are no specific processes mentioned in the literature for the control of acetylene emissions. Industry, however, does use absorber/scrubber systems in manufacturing operations for product purification. In this process diacetylene and acetylene are separated by using dimethyl formamide. Yields of acetylene ranging from 98.5 to 99.3 percent purity are accomplished by this method.[22] Estimated installed capital costs and operating costs for a general absorber/scrubber system are presented in Table 5.[23]

Table 5. ESTIMATED INSTALLED AND OPERATING COSTS FOR AN ABSORBER/SCRUBBER SYSTEM[23]

System capacity SCFM	1,000	4,000	8,000	20,000
Installed capital cost $	10,900	24,800	37,400	65,500
Annual operating cost $	5,900	12,100	19,500	40,200

SECTION III

REFERENCES

1. Chemical [illegible] Encyclopedic Treatise [illegible] Volume [illegible] Petroleum [illegible] Chemicals. New York, [illegible] and Sons Books, 1972. p. [illegible]

2. Gerarde, [illegible] Aliphatic (Open Chain) Hydrocarbons. In: Industrial Hygiene and Toxicology, Vol. [illegible] 2nd Rev. ed. Patty, F. A. (ed.). [illegible] Wiley & Sons, Inc., 1963. p. [illegible]

3. International Acetylene Association, Proceedings, [illegible]th Convention, Milwaukee, 1960. p. [illegible]-49.

4. Jones, A. T. Fatal Gassing in an Acetylene Manufacturing Plant. Arch Environ Health. 1:417-22, 1960.

5. American Industrial Hygiene Association. Hygienic Guide Series on Acetylene. Amer Ind Hyg Assoc J. 28:191-194, 1967.

6. Colldahl, H. The Pulmonary Elimination Capacity of Acetylene, Administered Intravenously in Saline Solution. Acta Med Scand. 169:27-[illegible], 1961.

7. Jernerud, B., G. Lundin, L.G.C.F. Pugh. Solubility of Acetylene in Lung Fi[illegible] as an Error in Cardiac Output Determination with the Acetylene Method. Acta Physiol Scand. 59:1-6, 1963.

8. The Toxic Substances List, 1974 Edition, HEW Publication No. (NIOSH), 74-134.

9. Air Quality Criteria for Hydrocarbons. National Air Pollution Control Administration, 1970, No. AP-64.

10. Abeles, F. B., H. E. Gahagan. Abscission: The Role of Ethylene, Ethylene Analogues, Carbon Dioxide, and Oxygen. Plant Physiol. 43:1255-58, 1968.

11. Burg, S. P., E. A. Burg. Molecular Requirements for the Biological Activity of Ethylene. Plant Physiol. 42:144-52, 1967.

12. Clayton, G. C. and T. S. Platt. Evaluation of Ethylene as an Air Pollutant Affecting Plant Life. Am Ind Hyg Assoc J. 28:151-160, 1967.

13. Altshuler, A. P. Reactivity of Organic Substances in Atmospheric Photo-oxidation Reactions. Public Health Service Publication No. 999-AP-14, 1965.

14. Air Quality Criteria for Photochemical Oxidants. National Air Pollution Control Administration. Publication No. AP-63, 1970.

15. Stephens, Edgar R. Hydrocarbons in Polluted Air. Summary Report. Coordinating Research Council, Statewide Air Pollution Research Center, California University. Riverside, California. NTIS Report No. PB-230 993. June 1973.

16. Turner, D. Bruce. Workbook of Atmospheric Dispersion Estimates. U.S. Environmental Protection Agency. Report No. AP-26. January 1973.

17. Ruch, Walter E. Quantitative Analysis of Gaseous Pollutants. Ann Arbor, Michigan, Ann Arbor-Humphrey Science Publishers. 1970.

18. Methods of Air Sampling and Analysis. American Public Health Association. Washington, D.C. 1972.

19. Chemical Profile. Schnell Publishing Co. July 1974.

20. Hahn, A. The Petrochemical Industry. McGraw-Hill, 1970.

21. Survey Reports on Atmospheric Emissions From the Petrochemical Industry, 1974. U.S. Environmental Protection Agency. Report No. EPA-450/3-73-005.

22. Faith, W. L. Industrial Chemicals. New York, John Wiley & Sons, 1965.

23. Hydrocarbon Pollutant Systems Study, Volume I. MSA Research Corp. October 1972.

12. Clayton, G. C. and T. S. Platt. Evaluation of Ethylene as an Air Pollutant Affecting Plant Life. Am Ind Hyg Assoc J. 28:151-160, 1967.

13. Altshuler, A. P. Reactivity of Organic Substances in Atmospheric Photo-oxidation Reactions. Public Health Service Publication No. 999-AP-14, 1965.

14. Air Quality Criteria for Photochemical Oxidants. National Air Pollution Control Administration. Publication No. AP-63, 1970.

15. Stephens, Edgar R. Hydrocarbons in Polluted Air. Summary Report. Coordinating Research Council, Statewide Air Pollution Research Center, California University. Riverside, California. NTIS Report No. PB-230 993. June 1973.

16. Turner, D. Bruce. Workbook of Atmospheric Dispersion Estimates. U.S. Environmental Protection Agency. Report No. AP-26. January 1973.

17. Ruch, Walter E. Quantitative Analysis of Gaseous Pollutants. Ann Arbor, Michigan, Ann Arbor-Humphrey Science Publishers. 1970.

18. Methods of Air Sampling and Analysis. American Public Health Association. Washington, D.C. 1972.

19. Chemical Profile. Schnell Publishing Co. July 1974.

20. Hahn, A. The Petrochemical Industry. McGraw-Hill, 1970.

21. Survey Reports on Atmospheric Emissions From the Petrochemical Industry, 1974. U.S. Environmental Protection Agency. Report No. EPA-450/3-73-005.

22. Faith, W. L. Industrial Chemicals. New York, John Wiley & Sons, 1965.

23. Hydrocarbon Pollutant Systems Study, Volume I. MSA Research Corp. October 1972.